ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). **instructions for completing this form can be found on the following pages.**

SECTION A PROPERTY INFORMATION					FOR INSURANCE COMPANY USE			
BUILDING OWNER'S NAME SO WHITE TAI					POLICY NUMBER			
STREET ADDRESS (Including Ap	COMPANY NAIC NUMBER							
OTHER DESCRIPTION (Lot and Block Numbers, etc.) LOT 14 WOOD LAND MEADOWS								
CITY	STATE WASHING	ZIP CODE						
SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION								
Provide the following from the proper FIRM (See Instructions):								
1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)			
530032	305	D	9/29/89	A-15				
7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: Feet NGVD (or other FIRM datum—see Section B, Item 7)								
SECTION C BUILDING ELEVATION INFORMATION								
 describes the subject building's reference level 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of feet NGVD (or other FIRM datum—see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is feet above or below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is feet above or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 								
4. Elevation reference mark used appears on FIRM: Yes No (See Instructions on Page 4)								
5. The reference level elevation is based on: A actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)								
6. The elevation of the lowest grade immediately adjacent to the building is: feet NGVD (or other FIRM datum-see Section B, Item 7).								
SECTION D COMMUNITY INFORMATION								
If the community official resistance is not the "lowest floor" as floor" as defined by the oracle. Date of the start of constructions.	s defined in the commun rdinance is:	nity's floodplain J.∟ feet NG\	management ordinand VD (or other FIRM datu	e, the elevation of	of the building's "lowest			

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

i certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

OCENTICADO MANGE			AMI 6 %	
BOLTON C. MINISTER	LIL 1	ENSE NUMBER (or	Affix Seal) WASH	
TITI F	COMPANY NAME			
PRESIDENT	MINISTER & GC	MESEL S	WENCHING	INC,
ADDRESS	CITY '			STATE ZIP
2208 E.EYERGREEN	BLYD VANC	1	w	ASH 98661
SIGNATURE	-f-	DATE 2/17/9	PHONE	-892-0732
Copies should be made of this Certificate for:	1) community official, 2	7		
COMMENTS:				
			1325 WASK	
				AT
		1/2	1/1/6	111.
			W 125-3	
		2 mg	CAMALLIAN.	53.
			EXPRES (P.1), 25, 1	m 5
ON SLAB	HTIW		ON PILES, PIERS, OR COLI	ILIAIC
A V	A		A	V
zones zones	T ZONES			ONES VAL
REFERENCE	2009 .	BASE	FERENCE LEVEL	REFERENCE
LEVEL	,	FLOOD ELEVATION		LEVEL
		uluu.		\\
				BASE
BASE FLOOD		ERENCE	M	FLOOD ELEVATION
ELEVATION REFERENCE ADJACENT LEVEL GRADE	GANDE W	<u></u>		M)
				M
	ī			
			1/2	ADJACENT
			₩ n	GRADE
The diagrams above illustrate the points at v	vhich the elevations should	d be measured in	n A Zones and V Zo	ones.
Elevations for all A Zones should be measure	ed at the top of the referen	nce level floor.		

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.